

## **POLYFREEZE GOLD READY-TO-USE (50/50) ANTIFREEZE & COOLANT**

PolyFreeze Gold 50/50 is the true UNIVERSAL full fill and TOP OFF Antifreeze/Coolant. It is the Ready-To-Use version of PolyFreeze Gold Full Strength Antifreeze, Pre-Diluted with deionized water for ANY VEHICLE.

- ALL AUTOMOBILE ENGINES - Meets the specifications for ALL auto manufacturers. This includes long life products such as GMAC - Dexcool, Ford and Daimler-Chrysler GO-5 type specifications and ASTM D-3306.
- ALL DIESEL ENGINES - PolyFreeze Gold is pre-charged with Supplemental Coolant Additive (SCA) including nitrites and molybdates that allow it to meet all heavy-duty diesel engine specifications. It can provide engine protection up to 600,000 miles with testing and SCA addition at 300,000 miles.
- ANY COLOR ANTIFREEZE - Can be mixed with any color antifreeze without causing the cooling system to turn a brown color.

Meets the following specifications:

ASTM D3306	ASTM D-4985
Ford ESE-M97B44-A	ASTM D-6210
Ford WSS-M97B44-B	Caterpillar EC-1/ELC
Ford WSS-M97B51-A1	TMC of ATA RP 329/330
Chrysler MS-9769	GMC 6277M
GO-5	



### **Specifications**

Appearance.....	Light Gold
Specific Gravity .....	1.060 - 1.070
Freezing Point, at 50% F .....	-34
pH at 50% .....	9.0 - 10.8
Foam Break Time at 50%, max sec .....	5
Reserve Alkalinity.....	5 - 7
Silicate Content, max. wt. % .....	0.005

\* Dex-Cool is a registered trademark of GM Corp. Long Life is not manufactured for or licensed by GM Corp.