

HEAVY DUTY GREEN

ANTIFREEZE / COOLANT CONCENTRATE

This premium quality antifreeze is designed for use in heavy-duty diesel, light duty diesel, and automotive engines. The inhibitor package contains a full charge of heavy duty chemical inhibitors to prevent liner pitting and corrosion. This antifreeze is low silicate, phosphate free, and is compatible with all SCA chemical filters.

For safety purposes this antifreeze is blended with a bittering agent.

Blended with proprietary additives, this antifreeze is designed to safely meet the performance specifications of (but not limited to):

ASTM D-6210
ASTM D-3306
ASTM D-4985
Detroit Diesel 7SE298
Cummins CES14603
Navistar
PACCAR

SAE1941
GM 1825M
GM 1899M
John Deere 8650-5
TMC RP 329
Freightliner 48-22880
MACK

CID A-A 52624A
Caterpillar
Case Corp MS1710
Ford New Holland 9-86
Thermo-King
Volvo GM
EMD M.I. 1748E

***De-ionized or distilled water is recommended when diluting any concentrated antifreeze to prevent damage from hard water.*

TYPICAL PROPERTIES

Appearance	Green
Specific Gravity @ 60/60 °F	1.110 – 1.150
Freeze Point, at 50% °F max	-34°
pH @ 50%	8.5 – 11.0
Reserve Alkalinity, min	7
Foam Break Time, ml/sec, max.....	150ml / 5 sec