



ORG CHEM Group, LLC

2406 Lynch Road • Evansville, IN 47711 • www.chem-group.com

COMPARISON OF SELECTED PROPERTIES

		Virgin DT-A	Reclaimed DT-A
Temperature Range, Non-Pressurized, °F (°C)	ASTM D2887	54-495 (13-257)	54-495 (13-257)
Pressurized, °F(°C)	ASTM D2887	495-750 (257-400)	495-750 (257-400)
Max Bulk Temperature, °F (°C)	ASTM D6743	750 (400)	750 (400)
Max Skin Temperature, °F (°C)	ASTM D6743	806 (430)	806 (430)
Minimum Pumping Temperature, 400 Cs KV, °F (°C)	ASTM D445	55 (13)	55 (13)
Pour Point, °F (°C)	ASTM D97	54 (13)	54 (13)
Minimum Flash Point, °F (°C)	ASTM D92	236 (114)	235 (113)
Specific Gravity @60 °F (15.5°C)	ASTM D1298	1.06	1.06
Composition		Di-Aryl Mixture	Di-Aryl Mixture
Appearance	Visual	Water White	Pale Yellow
Odor		Striking	Striking
Kinematic Viscosity, Cs 100°F (37.8°C)	ASTM D445	2.5	2.5
600°F (315°C)	ASTM D445	0.16	0.16
Vapor Pressure, psia, at 600°F (316°C)		106	106

Prepared: 03/31/2016

NOTE: the information contained herein is presented in good faith and believed to be correct as of the date hereof. CHEM Group does not guarantee performance results based upon reliance on this information and disclaims liability for any loss or damage arising out of any use of this information. CHEM Group makes no express or implied warranty as to the fitness, merchantability or other matters with respect to the information or products, except as set forth in CHEM Group's standard conditions of sales. Nothing contained herein is to be construed as a recommendation to use any product or process in conflict with any patent.