

Polyflo[®] 5



Product Data

Property	Test Method	Specifications
Specific Gravity, @ 60°F	ASTM D 1298	0.981 – 1.012
Viscosity, @ 40°C	ASTM D 445	4.0 – 6.0
Flash Point, °F	ASTM D 92	270 minimum

Description

Polyflo[®] 5 is a C₁₁-C₂₄ high flash aromatic naphtha solvent. The aromatic content of Polyflo 5 is typically >99%. The product has no detectable level of naphthalene at a detection limit of 500 ppm. Applications include refining, fuel, and lube additives, industrial cleaning, sealants, and as a processing fluid.

Shipping Information

Polyflo[®] 5 is available in rails cars (180,000 lbs net weight), trucks (45,000 lbs net weight), tote (2,300 lbs net weight), and drum (470 lbs net weight).

Safety and Handling Information

For specific information on the safe handling of this product, please, refer to the material safety data sheet. Copies are available upon request.

For Additional Information, please contact:



ORG CHEM Group, LLC.
2406 Lynch Road
Evansville, IN 47711
(800) 489-2306

Disclaimer

Polyflo[®] is a registered trademark of ORG CHEM Group, LLC. The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of CHEM Group and its subsidiaries. It is the responsibility of the user to comply with applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation or use any of the herein materials or processes in violation of existing or future patent.