



**CONVENTIONAL GREEN  
CONCENTRATE**

## PowerGard™ Premium Green Concentrate AntiFreeze

Is a premium ethylene glycol based antifreeze that provides all season protection and when used as directed, offers superior 5-way protection against:

- Freeze-up/Boil Over
- Scale Build Up
- Sludge/Clogging
- Wet Sleeve Liner Pitting
- Rust Corrosion

### ADVANTAGES

- Meets Light Duty ASTM D-3306 and Heavy Duty ASTM D-6210
- One product for Light Duty and Heavy Duty Applications.
- No need to add SCA's or chemical filters.
- Perfect choice for mixed fleets.
- Compatible with all Conventional Green Antifreeze.
- Phosphate free and meets low silicate standards.
- May be used in virtually any engine cooling system.

### SPECIFICATIONS

As an all purpose, conventional antifreeze, PowerGard Green Concentrate is blended with proprietary additives designed to safely meet the performance specifications of (but not limited to):

- ASTM D-3306
- ASTM D-6210
- Mack
- Orion/ MCI
- Ford ESE M97B44D
- Caterpillar
- Detroit Diesel
- Coaches
- Chrysler MS 7170
- GMC Truck
- GE Locomotive
- Freightliner
- GM 1825M
- John Deere
- Military CID
- International
- GM 1899M
- Case
- A-A52624-A
- TMC RP329



### TYPICAL PROPERTIES

DESCRIPTION	TYPICAL VALUES	TEST METHOD
Appearance	Visual	Green
Specific Gravity at 60/60°F	1.085-1.150	D 1122
Freeze Point, at 50% max	-34°F	D-3321
pH at 50% Solution	8.5-10.0	D-1287
Reserve Alaklinity min.	6	D-1121
Foam Test	150ml/5 sec	D-1881

**Available in Gallon Jugs, Drums, Totes and Bulk**



Are Trademarks of ORG Chem-Group, LLC



ORG Chem-Group  
11210 Solomon Road  
Troy, In, 47588  
812.547.7951

BOIL OVER PROTECTION	% of Cooling System capacity	PROTECTS FROM	
		Freezing Down to	Boiling Up to*
Using a 15 PSI Pressure Cap	40	-10 °F	259 °F
	50	-34 °F	265 °F
	60	-62 °F	270 °F

Cooling System Capacity in Quarts	Quarts of Antifreeze Required for Protection to Temperature (°F) Shown									
Quarts	3	4	5	6	7	8	9	10	11	
8	-7	-34								
9	0	-21	-50							
10	4	-12	-34	-62						
11	8	-6	-23	-47						
12	10	0	-15	-34	-57					
13		3	-9	-25	-45					
14		6	-5	-18	-34	-54				
15		8	0	-12	-26	-43	-62			
16		10	2	-8	-19	-34	-52			
17			5	-4	-14	-27	-42	-58		
18			7	0	-10	-21	-34	-50	-62	
19			9	2	-7	-16	-28	-42	-56	
20			10	4	-3	-12	-22	-34	-48	

For best overall protection, solution strengths within the YELLOW color band are recommended.

**50% SOLUTION RECOMMENDED TO OBTAIN 5-WAY PROTECTION.  
DO NOT EXCEED 70% CONCENTRATION OF ANTIFREEZE**