

PowerGard™ Premium Long Life 50/50 AntiFreeze

Used as directed, offers superior performance in virtually every light and heavy duty application. The proprietary inhibitor package is low silicate and phosphate and 2-EH free. Can be used as a top-off but to achieve maximum protection a complete flush and fill should be performed. PowerGard Premium Long Life Antifreeze provides protection against:

- · Freeze-up/Boil Over
- ·Scale Build Up
- ·Sludge/Clogging

- Wet Sleeve Liner Pitting
- Rust Corrosion
- ·Scale Build Up

ADVANTAGES

- Meets Light Duty ASTM D-3306 and Heavy Duty ASTM D-6210
- One product for Light Duty and Heavy Duty applications.
- Perfect choice for mixed fleets. No need to add SCA's.
- Blended with pure De-Ionized water for your quality needs.
- Phosphate free and low silicate the choice for Japanese and Korean models.
- Light Duty 5 years/150,000 miles Heavy Duty 3 years/300,000 miles.
- Compatible with hybrid and OAT coolants including Dexcool™

SPECIFICATIONS

PowerGard Long Life 50 is blended with proprietary additives designed to safely meet the performance specifications of (but not limited to):

- •ASTM D-3306
- •ASTM D-6210
- · Case New Holland · Komatsu
- Chrysler MS 7170 Caterpillar EC-1
- Volvo Trucks
- Navistar

- Ford WSS-M97B51 Detroit Diesel
- •TMC RP329 GE Locomotive

- •GM 1825M
- · Cummins Engine · Freightliner

- •GM 1899M
- John Deere
- Ford ESE-M97B44-D
- International
- Mercedes



TYPICAL PROPERTIES

DESCRIPTION	TYPICAL VALUES	TEST METHOD
Appearance	Visual	Orange/Red
Specific Gravity at 60/6	60°F 1.053-1.083	D 1122
Freeze Point, at 50% m	ax -34°F	D-3321
pH at 50% Solution	8.5-10.0	D-1287
Reserve Alaklinity min.	2.5	D-1121
Foam Test	150ml/5 sec	D-1881

Type of **Atmospheric** 14 LB. 15 LB. **Coolant Test** Pressure cap cap 265°F **Coolant Boiling** 224°F 262°F -34°F -34°F **Coolant Freezing** -34°F

BOIL OVER PROTECTION

Available in Gallon Jugs, Drums, Totes and Bulk





ORG Chem-Group 11210 Solomon Road Trov. In. 47588 GROUP 812.547.7951